

Wear parts for shotcrete equipment



Rubber plates

Sheet steel disc with vulcanized resistant rubber and inserted deflector plate
70-78 deg ShoreA +/- 0,5
Rubber surface grinded N6
Ready for installation

Top quality and durable for shotcrete machines of different producers, with or without greasing cup, available for:

OCMER (all types)
ALIVA AL-246
ALIVA AL-252 / AL-260 / AL-262
ALIVA AL-263
ALIVA AL-285



Rotor discs

Extra high resistant chromium steel (12 %)
Hardness HRC 62
Coplanar of +/- 0,05 mm
Grinded to N6
Ready for installation

Extra hardened steel quality for shotcrete machines of different producers

OCMER (all types)
ALIVA AL-246
ALIVA AL-252 / AL-260 / AL-262
ALIVA AL-263
ALIVA AL-285



Dry shotcrete nozzles

Made from resistant plastics
Galvanized shotcrete gun
Brass needle valve with brass hand wheel

Approved and tough quality for dry shotcrete
System ALIVA
Available for different diameters of the shotcrete hoses



Wet shotcrete nozzles

of Polyurethane
with flange 3", Ø 38 mm on the exit, without lip seal usable

Approved and tough quality for wet shotcrete
System Sika / Putzmeister



Pre wetting equipment SSG

For centric water injection into the shotcrete stream, no high pressure water pump necessary

Shotcrete equipment with pre wetting for dust- and rebound reduced dry shotcrete, very easy to install into spraying system as from OCMER, ALIVA, Meyco...



Shotcrete testing equipment

PenF 1000 N

Reversible display
Peak value
Battery operated
Removable handholds
Suitable also as balance (100 kg)

Penetration needle with digital display.
To identify the strength development of shotcrete according the „Austrian Guideline for Shotcrete“
Maximum load 1000 N (comply strength of appr. 1,5 N/mm²)

Distributor:

beton.Q Galehr KEG
Augarten 4
A 6824 Schlins
Tel. +43-5524/2018
Fax +43-5524/22545
Mail: beton.Q@vol.at